

EC- Declaration of conformity



PUKKILA OY AB
Pitkämäenkatu 9
FI-20250 TURKU

Manufacturing Unit: TURKU

Product:

“Dry-pressed ceramic tiles with low water absorption, E <0, 5%,
Group Bla , Annex G, (GL)

According to standard EN 14411 Ceramic tiles – Definition, classification, characteristics and marking products results consistent with Annex ZA and ZB.

Description and conditions applicable to the use of the product:

Ceramic tiles, for internal and external wall/ceiling finishes and floorings

Characteristics, which products complete

Characteristics	Declared value	Test method
Reaction to fire	A1 _{fl}	Decision 96/603/EEC
Breaking strength	Thickness < 7,5 : 700 N Thickness ≥ 7,5: 1300N	ISO 10545-4
Modulus of rupture	>35 N/mm ²	
Slipperiness	See product information	DIN 51130 / DIN 51097
Skid resistance	Not defined	
Bond strength	> 0,5 N/mm ²	For cementitious adhesives Class C2 (EN12004: 2001)
Thermal shock resistance	Passed	ISO 10545-9
Frost resistance	Passed	ISO 10545-12
Release of dangerous substances		
- release of cadmium	Not defined	ISO 10545-15
- release of lead	Not defined	ISO 10545-15

Notified laboratories:


CENTRO CERAMICO, CENTRO DI RICERCA, E SPERIMENTAZIONE
PER L'INDUSTRIA CERAMICA
Via Martelli, 26- 40138 Bologna

VTT, Technical Research Centre of Finland, Construction
PL 18011
FI-02044 VTT

Signature:


Name: Veikko Virta
Position: Production Manager
Date: 7.2.2007

Signature:


Name: Seppo Jokinen
Position: Technical Advice
Date: 7.2.2007